

ArcSafe



FSAMP14ECKIT1
ARCSAFE® AMPSHIELD ARC FLASH FACE SHIELD



OPTION: The ArcSafe® Streamlight® Flashlight is designed to provide high intensity illumination in low light areas or when working up close. Designed to be used with our ArcSafe® AmpShield Arc Flash Face Shield

ARCSAFE® AMPSHIELD ARC FLASH FACE SHIELD

The ArcSafe® AmpShield Arc Flash Face Shield offers a transparent alternative to the traditional green face shields. The highly transparent, nearly clear, arc flash protective shield provides enhanced visibility and heightened colour recognition.

- Highly transparent, grey nearly clear polycarbonate face shield provides enhanced visibility and heightened colour recognition.
- Includes cap bracket with slotted adaptor to fit selected hard hats. The adjustable slotted adaptor allows workers to comfortably adjust the position of the face shield when not in use or exposed to risk.
- The ergonomic, low profile transparent chin protector increases the field of view for the wearer as well as providing additional arc flash protection.
- Ability to add optional Streamlight® flashlight on either side of the face shield.
- Window Size: 25.4 x 50/8 x 0.15cm (10" x 20" x 0.06")
- Weight: 317g (11.20oz)

CERTIFICATIONS AND STANDARDS:

- PPE Cat Level 2 Protection
- 14 ca/cm2 ATPV
- Class 2 as per GS-ET-29
- NFPA 70E, ASTM F2178, EN 166, GS-ET-29 and ANSI-ISEA Z87.1-2017

CLEANING AND MAINTENANCE INSTRUCTIONS:

Clean and inspect after use. Clean with a damp cloth unless heavily soiled. Should further cleaning be required, clean with mild soap and water, pat dry. Disassemble if required, for cleaning or inspection. Inspect and replace any damaged or worn components.

PART NUMBER	FACE SHIELD	VISOR HOLDER	HARD HAT	BALACLAVA	KIT BAG
FSAMP14EC	•	•			
FSAMP14ECKIT1	•	•	•		•
FSAMP14ECKIT2	•	•	•	•	•

ArcSafe

ARCSAFE® STREAMLIGHT® FLASHLIGHT KIT

The ArcSafe® Streamlight® Flashlight is designed to provide high intensity illumination in low light areas or when working up close. Designed to be used with our ArcSafe® Lift Front Hoods and ArcSafe® AmpShield Face Shields and comes with an articulated light mount. ATPV 50 cal/cm².

- Thermoplastic Flashlight
- Polycarbonate lens
- LED Bulb
- Plastic Alloy articulated light mount
- ATPV 50 cal/cm².
- Uses 2 AAA batteries.
- Brightness: 60 lumens, 57m beam
- Run time: 16 hours
- Weight: Flashlight 54g (1.92 oz) with batteries
- Weight: Articulated Light Mount 11g (0.4 oz)

CERTIFICATIONS & STANDARDS

- 50 cal/cm² ATPV
- NFPA 70E



ASALMKIT
ARCSAFE® STREAMLIGHT® FLASHLIGHT KIT

PART NUMBER	ITEM
ASALMKIT	StreamLight Flashlight and bracket

The ArcSafe® Streamlight® Flashlight is designed to be used with our ArcSafe® AmpShield Arc Flash Face Shield or ArcSafe® Switching Hood with Lift Front