

HEARING PROTECTION

PROBAND™ FIXED HEADBAND EARPLUGS

PRODUCT DATA SHEET: HBEPA | HBEPAR

PRO
PRO CHOICE SAFETY GEAR

PRODUCT CODE:
HBEPA



PRODUCT CODE:
HBEPAR



FEATURES AND BENEFITS

- Certified to AS/NZS 1270:2002 Acoustic Hearing Protectors - Class 4 SLC_{80} 24dB.
- Hearing protection for noise levels to 105dB(A).
- Coloured blue for food safety.
- Disposable, PU foam pads.
- Provides wearer the highest level of protection for a headband earplug.
- Disposable PU foam pads are ergonomically designed to fit the ear for maximum protection.
- Pairs individually packaged.
- HBEPA kit includes complete unit and 1 pair off replacement pods



COMFORT



HI-VIS



HYGIENIC



REUSABLE

PRODUCT DETAILS

Material:	PU Foam
Length:	2.5cm
Diameter:	1.9cm
Weight:	20g
Colour:	Blue Foam Hi-Vis Orange Headband
Size:	Standard One Size

AVAILABLE IN

PRODUCT CODE	UOM	MOQ	CTN QTY
HBEPA	EACH	10	100
HBEPAR	EACH	50	500

MAINTENANCE

Before handling any earplugs, ensure hands are clean. Always check your earplugs and discard if damaged, worn or dirty. Silicone plugs can be washed if necessary. Single use ear plugs can cause health issues if used when dirty.

If kept clean and undamaged, silicone (reusable) ear plugs can be used many times over. Clean with mild soap/water and store in a case away from extreme heat and direct sunlight when not in use. On banded earplugs, clean and replace pads regularly as required.

APPLICATIONS

Agriculture, Construction, Fire Protection, Food Services, Forestry, Government, Emergency Services, Manufacturing, Medical, Military, Councils, Mining, Oil and Gas, Pharmaceutical, Steel and Metals, Transportation, Welding, Logistics and Transport, Automotive & Utilities.

TEST DATA

ATTENUATION TABLE (IN DECIBELS)							
Frequency Hz	125	250	500	1000	2000	4000	8000
Mean Attenuation	24.2	23.9	22.7	25.3	31.3	41.8	41.5
Standard Deviation	3.3	3.7	4.9	4.1	5.8	4.4	5.4
Mean-Minus-Standard Deviation Attenuations	20.9	20.2	17.8	21.2	25.5	37.4	36.1

SLC_{80} Value is 24 (Class 4)

STANDARDS

CERTIFIED TO:

Certified to AS/NZS 1270:2002 Acoustic Hearing Protectors - Class 4 SLC_{80} 24dB.

When selected, used & maintained as specified in AS/NZS 1269, this protector may be used in noise up to 105dB(A) assuming an 85dB(A) criterion. A lower criterion may require a higher protector class.



As/NZS 1270:2002
SMKH25293

PARAMOUNT SAFETY PRODUCTS AUSTRALIA

12 FELLOWSHIP ROAD,
GNANGARA, WA 6077
TECH SUPPORT: 1300 275 820
CUSTOMER SERVICE: 1300 770 723
EMAIL: INFO@PARAMOUNTSAFETY.COM

PARAMOUNT SAFETY PRODUCTS NEW ZEALAND

7 SIR WOOLF FISHER DRIVE, HIGHBROOK,
EAST TAMAKI, AUCKLAND 2013
TECH SUPPORT: 0800 888 778
CUSTOMER SERVICE: 0800 888 778
EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ

PROCHOICESAFETYGEAR.COM
PARAMOUNTSAFETY.COM

PRO
PRO CHOICE SAFETY GEAR
FROM
PARAMOUNT
SAFETY PRODUCTS